



(43) Date of publication:  
14.03.2001 Bulletin 2001/11

(51) Int Cl.<sup>7</sup>: **G11B 23/03**, G11B 7/00

(21) Application number: 99830572.6

(22) Date of filing: 10.09.1999

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU**  
**MC NL PT SE**  
 Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventor: **Perego, Luciano**  
**20050 Mezzago (MI) (IT)**


(74) Representative: **Tansini, Elio Fabrizio**  
C/O Bugnion S.p.A.  
Viale Lancetti, 19  
20158 Milano (IT)

**(71) Applicant: International Consulting S.r.l.  
20059 Vimercate (MI) (IT)**

(54) **Support card for data storage unit**

(57) A support card for digital memories comprises a flat support (2) of standardized rectangular conformation, having a first face (4) and a second face (5) and being provided with a centrally-disposed through opening (6). Formed in the first face (5) is a surface recess

(11) for receiving a DVD disc-half constituting a first storage unit (7). A steady engagement of the first storage unit (7) on the flat support (2) is achieved by a collar (13) disposed close to a centering through hole (8) presented by the storage unit (7) and intended for coupling, by forced fitting, with the through opening (6).



**BEST AVAILABLE COPY**

more apparent from the detailed description of a preferred but non-exclusive embodiment of a support card for a data storage unit in accordance with the present invention. This description will be taken hereinafter with reference to the accompanying drawings, given by way of non-limiting example, in which:

- Fig. 1 is an exploded perspective bottom view of a support card in accordance with the present invention;
- Fig. 2 shows the card in Fig. 1 with the optical memory unit mounted on the flat support;
- Fig. 3 shows the structure of a flat support being part of the subject card, to an enlarged scale relative to Figs. 1 and 2 and seen from the opposite side relative to Fig. 1;
- Fig. 4 is an exploded perspective top view of a support card in accordance with a second embodiment of the invention;
- Fig. 5 shows the card in Fig. 4 in an assembled condition;
- Fig. 6 shows a flat support being part of the card shown in Figs. 4 and 5, to an enlarged scale;
- Fig. 7 is a section taken along line VII-VII in Fig. 2, showing coupling between a first memory unit and the flat support, in accordance with a preferential embodiment of the invention;
- Fig. 8 shows an alternative embodiment in respect of Fig. 7;
- Fig. 9 is a section taken along line IX-IX in Fig. 5, showing a different embodiment for achieving coupling between the first memory unit and the flat support;
- Fig. 10 shows an alternative embodiment in respect of Fig. 8.

- [0011] With reference to the drawings, a support card for a data storage unit in accordance with the present invention has been generally identified by reference numeral 1.
- [0012] Card 1 essentially comprises a flat support 2, preferably made of plastic material, having a peripheral edge of a substantially rectangular profile defined by minor sides 3a and major sides 3b preferably of standard-sized sizes, corresponding to those of a conventional credit card.
- [0013] The peripheral edge 3a, 3b delimits, on the flat support 2, respectively opposite first 4 and second 5 faces having a through opening 6 preferably disposed at a centered position in the flat support 2. In more detail, the through opening 6 has a geometric axis "X" intersecting the crossing point between the diagonals in the rectangular configuration of the flat support 2.
- [0014] The first face 4 is advantageously intended for carrying a first data storage unit 7, hereinafter referred to as first storage unit, circumscribing the through opening 6.
- [0015] The first storage unit 7 is preferably of a disc-

[0001] The present invention relates to a support card for a data storage unit, of the type comprising the features set forth in the preamble of claim 1.

[0002] It is known that there are different types of cards of standardized rectangular shape, usually used as credit cards or telephone cards for example, which are essentially defined by a plate-like or flat support of plastic material with which a digital memory unit is associated.

[0003] In a first known type of card, the digital memory essentially consists of a magnetic band extending over one of the two opposite faces of the flat body, parallelly of one of the major sides of said body.

[0004] In a second known type of card commercially identified as "Smart Card", the digital memory is essentially made up of a microchip incorporated into the thickness of the flat body and having contact elements appearing on one of the faces of the flat body itself.

[0005] Also proposed in recent times have been cards of standardized rectangular shape in which the digital memory is of the optical type, i.e. of the type commonly utilized in manufacturing compact discs.

[0006] Embodiments of these cards are described in Patent Applications JP 4040586 and WO 99/00765. More particularly, differences as compared with the features encountered with reference to compact discs. In conclusion, a known card with an optical memory essentially consists of a compact disc or rectangular formation, in which the area intended for data storage is delimited by an annulus substantially tangent to the major sides of the card and concentric with a through opening disposed at a centered position on the card itself.

[0007] Appropriate centering elements, embodied for example by ridges in the form of an arc of a circle or projections of different shapes are arranged on a readable face of the card, intended for resting on an extractable tray being part of an usual reading unit for compact discs, in order to enable correct positioning of the card itself on said tray.

[0008] After the above statements, the Applicant has wished to analyse the possibility of providing a card with greatly improved versatility of use and memory capabilities as compared with the cards of the known art. In particular, the Applicant has aimed at enabling coexistence of several memory units even of different typologies on one and the same card, as well as the opportunity of omitting, removing and/or replacing at least one of the memory units to be combined with the card itself.

[0009] In more detail, it is an object of the present invention to provide a support card for data storage unit, comprising the features set forth in the characterizing part of claim 1.

[0010] Further features and advantages will become

shaped type, i.e. it comprises a plate-like body 8 having a centering through hole 9 and at least one area 10 for data storage, preferably of the optical type, such disposed as to form an annulus extending concentric with the centering through hole 9 and substantially tangent to the major sides 3b of the flat support 2.

[0016] In particular, it is preferably provided for the first storage unit 7, or at least the plate-like body 8 thereof, to be essentially defined by a DVD (digital versatile disc) disc-half the outer diameter of which substantially corresponds to the size of the minor sides 3a of the flat support 2. To the ends of the present description, by "disc-half" it is intended one of the two disc-shaped elements that are usually coupled in mutual superposition relationship when DVDs following conventional techniques are made. In this connection please see document EP 866450 for further explanations and information on how DVDs are made.

[0017] The plate-like body 8 preferably has a circular conformation, delimited by an outer circumferential edge 8a, but the plate-like body may also have a different conformation, a quadrangular conformation for example, provided it is contained within the extension of the perimetral edge 3a, 3b of the flat support 2.

[0018] Disposed on the first face 4 of the flat support 2, at the through opening 6, is means for engagement of the first storage unit 7, preferably comprising a surface recess 11 formed on the first face itself. The surface recess 11 is able to house the first storage unit 7 when the latter, through a locating surface 7a thereof, is brought in abutment on the surface recess itself.

[0019] Preferably, the shape of the surface recess 11 matches that of the first storage unit 7 and its depth corresponds to the thickness of said storage unit. In this way the first storage unit 7, when housed in the surface recess 11, has a reading surface 7b disposed flush with the first face 4 of the flat support 2.

[0020] In particular, in the embodiment shown, the surface recess 11 has a circular conformation and is delimited by a circumferential ridge 12 substantially tangent to the major sides 3b of the flat support 2.

[0021] Advantageously, engagement of the first storage unit 7 with the flat support 2 further involves the aid of mechanical-interfacing means comprising a fitting element for example, for engagement between the storage unit itself and the support card 1, preferably in a removable manner.

[0022] This mechanical-interfacing means preferably comprises a collar 13 axially projecting from the locating surface 7a at the centering through hole 9 having an inner diameter corresponding to that of the centering hole usually provided in a conventional compact disc or DVD. Collar 13 defines a shoulder 13a facing away from the geometric axis of the through hole. Shoulder 13a is able to cooperate with an inner circumferential edge 6a of the through opening 6 to accomplish a tight mechanical-interference fit with said opening.

[0023] In a preferential embodiment shown in Fig. 7,

shoulder 13a of collar 13 has a substantially cylindrical conformation in the same manner as the inner circumferential edge 6a of the through opening 6. The outer diameter of collar 13 is slightly greater than the inner diameter of opening 6, so as to carry out a tight interference fit of the collar into the opening.

[0024] In accordance with an alternative embodiment shown in Fig. 8, it may be advantageously provided that shoulder 13a defined by collar 13 and/or the inner circumferential edge 6a of the through opening 6 should be of truncated conical form. In this manner shoulder 13a defines an undercut turned towards the flat body 8, whereas the inner circumferential edge 6a defines an undercut turned towards the second face 5 of the flat support 2. Due to the presence of these undercuts a mechanical-interference snap fitting of collar 13 in opening 6 occurs.

[0025] To make snap-fitting easier, radial cuts may be advantageously arranged at collar 13 and/or opening 6, which cuts divide the collar itself and/or the inner circumferential edge 6a into a plurality of elastically-deformable portions in the form of an arc of a circle.

[0026] In a different embodiment, shown in Figs. 4, 5, 9 and 10, instead of collar 13 associated with the first memory unit 7 at least one grip lug 14 formed at the inner circumferential edge 6a of said through opening 6 is provided to be arranged. The grip lug 14, preferably having an annular conformation concentric with the through opening 6, defines a coupling ridge 14a facing away from the geometric axis X of the through opening 6, to engage, by interference fit, the centering hole 9 arranged in the first storage unit 7. In this embodiment, the through opening 6 will have the same inner diameter as the centering hole usually provided in compact discs or DVDs, whereas the centering hole 9 arranged in the first storage unit 7 will have a conveniently bigger diameter.

[0027] In this case too, both the grip lug 14 and the centering hole 9 may have a cylindrical configuration, with diameters slightly differentiated from each other to cause mutual coupling by forced fitting (Fig. 9). Alternatively, the grip lug 14 and/or centering hole 9 may be of truncated conical form as shown in Fig. 10, so as to define mutually opposite undercuts turned towards the second face 5 of the flat support 2 and the reading surface 7b of the first storage unit 7, respectively.

[0028] In addition to, or in place of collar 13 and/or the grip lug 14, the outer circumferential edge 8a of the plate-like body 8 and the circumferential ridge 12 of the surface recess 11 could be such arranged that mutual engagement by mechanical-interference fit will occur. Said outer circumferential edge 8a and circumferential ridge 12 may have a cylindrical configuration, with differentiated diameters to obtain forced coupling of the plate-like body 8 into the surface recess 11. Alternatively, the outer circumferential edge 8a and/or circumferential ridge 12 may have, at least as regards part of their circumferential extension, a frusto-conical conforma-

tion, to form mutually opposite undercuts turned towards the reading surface 7b and the surface recess 11, respectively.

[0029] Further associated with card 1 may be means 15, 16 for centering of the flat support 2 in a reading and/or data recording device on the first storage unit 7, not shown as known per se and conventional. Advantageously, this centering means 15, 16 may comprise centering shoulders 15 defined by auxiliary surface recesses 16, of a curved profile for example, formed in the first face 4 close to the minor sides 3a of the peripheral edge of the flat support 2.

[0030] In addition, associated with the support card 1 may advantageously be at least a further data storage unit 17 accessible from the second face 5 of the flat support 2. This further storage unit 17 can be advantageously made in the form of a microchip incorporated into the flat support 2, within a seal arranged therein, and having contact elements 17a appearing from the second face 5.

[0031] The present invention achieves the intended purposes.

[0032] Unlike the known art, in which any type of memory must necessarily be accomplished as a single unit with the flat support of the card, the invention enables a memory unit, in particular of the optical type, to be associated with the card, subsequently to production of the card itself. This circumstance opens a great number of new possibilities of use of the cards as digital memory media.

[0033] In particular, it is for example possible to arrange a card provided with a fixed digital storage unit, of the microchip type for example, with an optical memory, optionally interchangeable, may be associated in case of need.

[0034] An optical memory made in the form of a DVD disc-half can also advantageously coexist with a microchip memory even if, as it appears from the depicted examples, these memories extend over mutually superposed regions on the flat support. This would not be possible if the optical memory were made in the form of a compact disc, because thickness of said memory, corresponding to the overall thickness of the card, would involve penetration, by the microchip memory, into regions intended for receiving optical data.

[0035] On the contrary, due to use of a DVD disc-half, free in the flat support for housing the microchip memory of a thickness of 0.5 mm, a sufficient thickness is left without the latter projecting in the surface recess 11 and thereby occupying regions intended for the optical memory. In this connection it is to be noted that, due to dimensional standardization of the cards of the type in reference, thickness of same must not exceed 1.2 mm, the microchip memory only engaging a thickness of about 0.5 mm.

[0036] It should be also appreciated that since several memory units can be integrated into one and the same card, there will be an increase in the amount of data stored.

## Claims

able on the card itself. In addition, with use of a DVD optical memory, storage capacities close to about 1 GB may be easily obtained.

1. A support card for data storage units, comprising a plate-like or flat support (2) having a peripheral edge of substantially rectangular profile (3a, 3b) defining respectively opposite first and second faces (3a, 3b) and a through opening (6) through said first and second faces (4, 5), at least said first face (4) being intended for carrying a data storage unit (7) circumscribing said through opening (6), characterized in that it further comprises means (11) for engagement of said data storage unit (7), disposed on said first face (4) at the through opening (6).

2. A support card as claimed in claim 1, wherein said engagement means comprises a surface recess (11) formed in the first face (4) to house said data storage unit (7).

3. A support card as claimed in claim 2, wherein said surface recess (11) has a circular conformation.

4. A support card as claimed in claim 3, wherein said surface recess (11) is delimited by a circumferential ridge (12) substantially tangent to the major sides (3a) of said peripheral edge of rectangular profile of the flat support (2).

5. A support card as claimed in claim 4, wherein said circumferential ridge (12) is arranged to engage, by interference fit, an outer circumferential edge (8a) of said data storage unit (7).

6. A support card as claimed in claim 5, wherein said circumferential ridge (12) forms an undercut turned towards said surface recess (11).

7. A support card as claimed in claim 1, wherein said engagement means comprises an inner circumferential edge (6a) of said through opening (6) arranged to engage, by interference fit, a collar (13) projecting from said data storage unit (7).

8. A support card as claimed in claim 7, wherein the edge (6a) of said through opening (6) forms an undercut turned towards the second face (5) of the flat support (2).

9. A support card as claimed in claim 1, wherein said engagement means comprises at least one grip lug (14) formed at an inner circumferential edge (6a) of said through opening (6) and defining a coupling

ridge (14a) facing away from a geometric axis (X) of said through opening (6) to get engaged by interference fit in a centering hole (9) provided in said data storage unit (7).

10. A support card as claimed in claim 9, wherein said grip lug (14) has an annular conformation concentric with said through opening (6).

11. A support card as claimed in claim 9, wherein said coupling ridge (14a) forms an undercut turned towards the second face (5) of the flat support (2).

12. A support card as claimed in claim 1, further comprising another data storage unit (17) accessible from said second face of the flat support (2).

13. A support card as claimed in claim 12, wherein said further storage unit (17) is made in the form of a microchip incorporated in the flat support (2) and having contact elements (17a) appearing on said second face (5).

14. A support card as claimed in claim 1, wherein said through opening (6) is disposed concentric with the perimetral edge (3a, 3b) of the flat support (2).

15. A support card as claimed in claim 1, further comprising means for centering the flat support (2) in a reading device of said storage unit.

16. A support card as claimed in claim 15, wherein said centering means comprises centering shoulders defined by auxiliary surface recesses present in said first face (4) close to the minor sides (3a) of said perimetral edge of rectangular profile (3a, 3b).

17. A support card as claimed in claim 1, wherein said storage unit (7) comprises:

- a plate-like body (8) having a centering through hole (9);
- at least one region (10) intended for data storage and extending concentric with said centering through hole (9);
- mechanical-interfacing means (13) for engagement of said storage unit (7) on a support card (1).

18. A support card as claimed in claim 17, wherein said mechanical-interfacing means comprises at least one tight fitting element (13).

19. A support card as claimed in claim 17, wherein said mechanical-interfacing means comprises a collar (13) axially projecting at said centering through hole (9) and defining a shoulder (13a) facing away from a geometric axis of the through hole (9) and ar-

ranged to get engaged by interference fit in said through opening (6).

20. A support card as claimed in claim 19, wherein said shoulder (13a) defines an undercut turned towards the plate-like body (8).

21. A support card as claimed in claim 17, wherein said mechanical-interfacing means comprises an edge of said centering through hole (9) arranged to engage by interference fit a grip lug (14) being part of said engagement means disposed on said first face (4) of the flat support (2).

22. A support card as claimed in claim 21, wherein the edge of said through hole (9) forms an undercut turned towards a reading face (7b) of said storage unit (7).

23. A support card as claimed in claim 17, wherein said mechanical-interfacing means comprises an outer circumferential edge (8a) of said plate-like body (8), arranged to engage by mechanical-interference fit with a circumferential ridge (12) presented by said flat support (2).

24. A support card as claimed in claim 23, wherein said outer circumferential edge (8a) defines an undercut turned towards a reading face (7b) of said plate-like body (8).

25. A support card as claimed in claim 17, wherein said plate-like body (8) is essentially defined by a DVD disc-half.





FIG 4











FIG 5











DOCUMENTS CONSIDERED TO BE RELEVANT	
Category	Citation of document with indication, where appropriate, of relevant passages
X	PATENT ABSTRACTS OF JAPAN vol. 007, no. 070 (P-185), 23 March 1983 (1983-03-23) & JP 57 212669 A (MATSUSHITA DENKI SANGYO KK), 27 December 1982 (1982-12-27) * abstract *
X	US 4 903 256 A (NAKAHARA TAKASHI) 20 February 1990 (1990-02-20) * claim 1; figures 1-4 *
X	PATENT ABSTRACTS OF JAPAN vol. 011, no. 248 (P-604), 13 August 1987 (1987-08-13) & JP 62 054881 A (SONY CORP.), 10 March 1987 (1987-03-10) * abstract *
A	GB 2 059 666 A (MATSUSHITA ELECTRIC IND CO LTD) 23 April 1981 (1981-04-23) * claim 1; figures 2, 4 *
A	WO 97 21219 A (MEM CARD COMPUTER MEMORY SYSTE; WEINBERGER ZVI (IL); HOZATSKY LEV) 12 June 1997 (1997-06-12) * claim 1; figure 1 *
A	PATENT ABSTRACTS OF JAPAN vol. 1996, no. 06, 28 June 1996 (1996-06-28) & JP 08 031134 A (VAN P R KK), 2 February 1996 (1996-02-02) * abstract *
--- -/-	
The present search report has been drawn up for all claims	
Place of search	
BERLIN	
Date of completion of the search	
13 January 2000	
Examiner	
Bernas, Y	
T: theory or principle underlying the invention, or earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons A: technological background O: non-written disclosure P: intermediate document	
X: particularly relevant taken alone Y: particularly relevant & combined with another document of the same category	
CLASSIFICATION OF THE APPLICATION (INCL.7)	
G11B23/03 G11B7/00	
TECHNICAL FIELDS SEARCHED (INCL.7)	
G11B	



European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 99 83 0572

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	PATENT ABSTRACTS OF JAPAN vol. 009, no. 221 (P-386), 7 September 1985 (1985-09-07) & JP 60 079581 A (DAINIPPON INSATSU KK), 7 May 1985 (1985-05-07) * abstract *	1	
A	----- PATENT ABSTRACTS OF JAPAN vol. 010, no. 198 (P-476), 11 July 1986 (1986-07-11) & JP 61 039990 A (DAINIPPON PRINTING CO LTD), 26 February 1986 (1986-02-26) * abstract *	1	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 13 January 2000	Examiner Bernas, Y
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03.02 (P/C01)

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family (member's)	Publication date
JP 57212669 A	27-12-1982	JP 1284510 C	09-10-1985
		JP 6008546 B	04-03-1985
		AU 544979 B	27-06-1985
		AU 8492582 A	23-12-1982
		CA 1189616 A	25-06-1985
		DE 3222844 A	27-01-1983
		FR 2508220 A	24-12-1982
		GB 2103862 A,B	23-02-1983
		NL 8202480 A,B,	17-01-1983
		NL 8802984 A	03-04-1989
		US 4525758 A	25-06-1985
US 4903256 A	20-02-1990	JP 63228479 A	22-09-1988
		JP 63106976 A	12-05-1988
		DE 3750420 D	29-09-1994
		DE 3750420 T	26-01-1995
		EP 0265274 A	27-04-1988
JP 62054881 A	10-03-1987	JP 1911694 C	09-03-1995
		JP 6036296 B	11-05-1994
GB 2059666 A	23-04-1981	JP 1180575 C	09-12-1983
		JP 54019705 A	14-02-1979
		JP 58008041 B	14-02-1983
		JP 1190666 C	13-02-1984
		JP 54019706 A	14-02-1979
		JP 58023643 B	17-05-1983
		JP 1177958 C	30-11-1983
		JP 54019707 A	14-02-1979
		JP 58008042 B	14-02-1983
		JP 1177959 C	30-11-1983
		JP 54019708 A	14-02-1979
		JP 58008043 B	14-02-1983
		JP 1177960 C	30-11-1983
		JP 54019709 A	14-02-1979
		JP 58008044 B	14-02-1983
		CA 1106665 A	11-08-1981
		DE 2830880 A	18-01-1979
		FR 2397649 A	09-02-1979
		GB 2001191 A,B	24-01-1979
		US 4195844 A	01-04-1980
WO 9721219 A	12-06-1997	AU 7586296 A	27-06-1997
		EP 0864152 A	16-09-1998
JP 08031134 A	02-02-1996	NONE	

EP 1 083 563 A1

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 83 0572

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

13-01-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
JP 60079581 A	07-05-1985	NONE	
JP 61039990 A	26-02-1986	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**This Page Blank (uspto)**

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

**This Page Blank (uspto)**